

Subtile pendant/surface luminaire

MODUS DON5000, lenght 1355mm, LED 830, black body, black optic 80°, DALI

Code: DON5000M3CC80/DALI
EAN: 8596099143718



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	4700
System power (W):	37	Luminaire efficacy (lm/W):	127
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP20
Color housing:	Black	Suitable for suspended mounting:	Yes
Material housing:	Aluminium		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast

Optical system

Optical system:	C80	Light outlet:	Direct
Anti-glare limiting UGR:	16	Light sharing:	Symmetric
Fit for monitor workplace:	Yes		

Dimensions

Length (mm):	1358	Width (mm):	48
Height/depth (mm):	57	Weight (kg):	3

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	Dimming DALI:	Yes