The Light Group

Developed by The Light Group

IK10 CE IP65

The Light Group | SLC1408



SLC Dio White 1760/1900/1890 lm 2700/3200/4000K Ra>80 Not dimmable IP65 OP

Outdoor luminaire for wall or ceiling. Easy installation. Has through wiring for both concealed and open installation. Robust luminaire with IK10 and IP65.

Electrical

Input	220-240V 50/60Hz
Rated power	18 W
Control type	Not dimmable
MAX. qty on 16A Circuit Breaker (Type C)	53
Expected lifetime (25°C)	100 000 hours
Light reduction (25°C)	L90B50
Expected lifetime at max Ta	50.000
Light reduction at max Ta	L90B50
Operating temperature (Ta)	–20°C - +45°C
Insulation class	Class II

Light technic

Lumen	1760/1900/1890 lm
Efficacy	112 lm/W
Colour temperature	2700/3200/4000K
Colour rendering (CRI/Ra)	Ra>80
MacAdam (SDCM)	3
Dimmable	No
Optics/Diffuser	Opal

Mechanical

Installation Type	Surface
Material, main	Plastic
Material, optics	Polycarbonate
IP rating	IP65
IK grade	IK10
Colour	White
RAL	RAL9016
UV-resistant	Yes
Suitable for	Indoor / Outdoor

Dimensions

Height	59 mm
Width	275 mm
Length	275 mm
Product net weight	866 g
Diameter	275 mm

The Light Group GmbH
Am Schafbrinke 62 | 30519 Hannover | Germany
www.thelightgroup.de

The Light Group AS
Mjåvannsvegen 175 | 4628 Kristiansand | Norway
www.tlg.no