

IP68 IP68 perfect for internal or external applications

 Coastal protected

IK08 IK08 impact protection - walk over (Stainless Steel only)



WARRANTY

Warranty 7 years

FEATURES & BENEFITS

- Supplied complete with installation tube
- Low voltage ground light
- Walk over ground light ideal for paths or steps
- SDCM3 ensuring uniform light appearance and consistency
- CRI 80 providing true colour appearance
- Available in a new 2200K setting to create a warm and cosy environment with minimal disruption to natural habitat
- Long-lifetime of 70,000hrs
- Available in an array of colours

PATENT: **GB2544975 EP3176502**




Stainless Steel



Antique Brass



Black



GL100 2 WINDOWS 1 DIRECTION

Domed Ground Light

FEATURES

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	150mA / 250mA / 350mA / 500mA / 700mA DC
Maximum Ambient Temperature	55°C
Weight	GL100AB: 231g, GL100BK: 214g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless Steel
UK Bathroom Zone	0
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	Im	Im/W	Energy
GL100SS2W30	Stainless steel 316	2 Windows 1 Direction	75°	0.7W (250mA)	3000K	5	6	
				1W (350mA)	3000K	6	6	
				1.5W (500mA)	3000K	9	6	
				2.2W (700mA)	3000K	11	5	
GL100SS2W40	Stainless steel 316	2 Windows 1 Direction	75°	0.4W (150mA)	4000K	3	8	
				0.7W (250mA)	4000K	5	7	
				1W (350mA)	4000K	7	7	
				1.5W (500mA)	4000K	9	6	
GL100AB2W22	Antique brass	2 Windows 1 Direction	75°	0.4W (150mA)	2200K	3	6	
				0.7W (250mA)	2200K	4	6	
				1W (350mA)	2200K	6	6	
				1.5W (500mA)	2200K	8	5	
GL100AB2W27	Antique brass	2 Windows 1 Direction	75°	0.4W (150mA)	2700K	3	6	
				0.7W (250mA)	2700K	4	6	
				1W (350mA)	2700K	6	6	
				1.5W (500mA)	2700K	8	5	
GL100AB2W30	Antique brass	2 Windows 1 Direction	75°	0.4W (150mA)	3000K	3	7	
				0.7W (250mA)	3000K	5	6	
				1W (350mA)	3000K	6	6	
				1.5W (500mA)	3000K	9	6	
GL100AB2W40	Antique brass	2 Windows 1 Direction	75°	0.4W (150mA)	4000K	3	8	
				0.7W (250mA)	4000K	5	6	
				1W (350mA)	4000K	6	6	
				1.5W (500mA)	4000K	9	6	

GL100 Modular creates a grazing light effect from a dome available in five different window styles, and four colour temperatures range from 2200K/2700K/3000K/4000K to suit a wide range of applications. Plus, with an IP68 rating, costal protection, and IK07, this ground light can be installed in both interiro and external segregation, making it an all-round solution. Also now available in an array of colours: stainless steel, antique brass, black, and bronze.

		Direction			0.7W (250mA)	4000K	5	7	
					1W (350mA)	4000K	7	7	
					1.5W (500mA)	4000K	9	6	
					2.2W (700mA)	4000K	12	6	
GL100BK2W22	Black	2 Windows 1 Direction	75°	0.4W (150mA)	2200K	3	6		
				0.7W (250mA)	2200K	4	6		
				1W (350mA)	2200K	6	6		
				1.5W (500mA)	2200K	8	5		
				2.2W (700mA)	2200K	10	5		
GL100BK2W27	Black	2 Windows 1 Direction	75°	0.4W (150mA)	2700K	3	6		
				0.7W (250mA)	2700K	4	6		
				1W (350mA)	2700K	6	6		
				1.5W (500mA)	2700K	8	5		
				2.2W (700mA)	2700K	10	5		
GL100BK2W30	Black	2 Windows 1 Direction	75°	0.4W (150mA)	3000K	3	7		
				0.7W (250mA)	3000K	5	6		
				1W (350mA)	3000K	6	6		
				1.5W (500mA)	3000K	9	6		
				2.2W (700mA)	3000K	11	5		
GL100BK2W40	Black	2 Windows 1 Direction	75°	0.4W (150mA)	4000K	3	8		
				0.7W (250mA)	4000K	5	7		
				1W (350mA)	4000K	7	7		
				1.5W (500mA)	4000K	9	6		
				2.2W (700mA)	4000K	12	6		
GL100SS2O22	Stainless steel 316	2 Windows 2 Directions	75°	0.4W (150mA)	2200K	3	6		
				0.7W (250mA)	2200K	4	6		
				1W (350mA)	2200K	6	6		
				1.5W (500mA)	2200K	8	5		
				2.2W (700mA)	2200K	10	5		
GL100SS2O27	Stainless steel 316	2 Windows 2 Directions	75°	0.4W (150mA)	2700K	3	6		
				0.7W (250mA)	2700K	4	6		
				1W (350mA)	2700K	6	6		
				1.5W (500mA)	2700K	8	5		
				2.2W (700mA)	2700K	10	5		
GL100SS2O30	Stainless steel 316	2 Windows 2 Directions	75°	0.4W (150mA)	3000K	3	7		
				0.7W (250mA)	3000K	5	6		
				1W (350mA)	3000K	6	6		
				1.5W (500mA)	3000K	9	6		
				2.2W (700mA)	3000K	11	5		
GL100SS2O40	Stainless steel 316	2 Windows 2 Directions	75°	0.4W (150mA)	4000K	3	8		
				0.7W (250mA)	4000K	5	7		
				1W (350mA)	4000K	7	7		
				1.5W (500mA)	4000K	9	6		
				2.2W (700mA)	4000K	12	6		
GL100AB2O22	Antique brass	2 Windows 2 Directions	75°	0.4W (150mA)	2200K	3	6		
				0.7W (250mA)	2200K	4	6		
				1W (350mA)	2200K	6	6		
				1.5W (500mA)	2200K	8	5		
				2.2W (700mA)	2200K	10	5		
GL100AB2O27	Antique brass	2 Windows 2 Directions	75°	0.4W (150mA)	2700K	3	6		
				0.7W (250mA)	2700K	4	6		
				1W (350mA)	2700K	6	6		
				1.5W (500mA)	2700K	8	5		
				2.2W (700mA)	2700K	10	5		

Energy rating is a reflection of the LED light source		2 Windows 2					
GL100AB2O30	Antique brass	Directions	75°	0.4W (150mA)	3000K	3	

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

GL100 Modular creates a grazing light effect from a dome available in five different window styles, and four colour temperatures range from 2200K/2700K/3000K/4000K to suit a wide range of applications. Plus, with an IP68 rating, costal protection, and IK07, this ground light can be installed in both interiro and external segregation, making it an all-round solution. Also now available in an array of colours: stainless steel, antique brass, black, and bronze.