


LED waterproof light fitting

MODUS PL 10000, wide body 1575mm, LED 840 ,
body PE, opal PC cover, IP65, driver 2100mA DALI

Code: PL10000L2W4DALI

EAN: 8596099023324

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	11000
System power (W):	70	Luminaire efficacy (lm/W):	157
Rated lifetime L70/B50 (h):	100000	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes		
Material housing:	Plastic		
Light source included:	Yes	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Rated ambient temperature (°C):	-10...+35
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast
Light source type:	1990660584001	Energy efficiency class:	C

Optical system

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

Dimensions

Length (mm):	1575	Width (mm):	135
Height/depth (mm):	100	Weight (kg):	2,8

Electrical values

Protection class:	I	Dimmable:	Yes
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Dimming DALI:	Yes		
Indoor use only:	Yes		