



SLC Space Ø300 Black 2490lm 2700/3200/4000K Ra>80 Trailing edge IP20 OP

The Space is a sleek, low-profile LED fixture mounted on the ceiling or the wall. It is well-suited for private homes, residences, corridors, staircases, bathrooms, and closets. The fixture comes with an opal diffuser to provide a pleasant lighting experience. Available in two sizes: Diameter 235 mm and Diameter: 300 mm. The Space is designed and constructed for easy installation in all situations, whether it involves open wiring, old ceiling boxes, or DCL outlets.

Electrical

Input	220-240V 50/60Hz
Rated power	22 W
Control type	Trailing edge
MAX. qty on 16A Circuit Breaker (Type C)	45
Expected lifetime (25°C)	100 000 hours
Light reduction (25°C)	L90B10
Light reduction at max Ta	L80B10
Operating temperature (Ta)	-20°C - +40°C
Insulation class	Class II

Light technic

Luminous flux	2490 lm
Efficacy	116 lm/W
Colour temperature	2700/3200/4000K
Colour rendering (CRI/Ra)	Ra>80
MacAdam (SDCM)	3
Beam angle fixed	120 °
Dimmable	Yes
Glare (UGR)	UGR<25
Optics/Diffuser	Opal

Mechanical

Installation Type	Surface-mounted roof/wall
Material, main	Plastic
Material, optics	Plastic
IP rating	IP20
IK grade	IK06
Colour	Black

Dimensions

Width	300 mm
Length	300 mm
Product net weight	992 g
Diameter	300 mm