

OS250D03P



General Information

Extended Product Type:	OS250D03P
Product ID:	1SCA022719R0090
EAN:	6417019230580
Catalog Description:	OS250D03P Switch fuse
Long Description:	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

Categories

Products » Low Voltage Products and Systems » Switches » Switch Fuses

Ordering

EAN:	6417019230580
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	208 mm
Product Net Height:	193 mm
Product Net Depth:	154 mm
Product Net Weight:	4.3 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	204 mm
Package Level 1 Height:	167 mm
Package Level 1 Length:	275 mm
Package Level 1 Gross Weight:	4.3 kg
Package Level 1 EAN:	6417019230580

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-05-01
---------------------	--

Additional Information

Conventional Free-air Thermal Current (I_{th}):	q=40°C 250 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 250 A
Fuse Size:	0, 1
Fuse System:	DIN
Fuse Type:	DIN
Handle Type:	Pistol Handle
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Mounting Type:	Normal
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Operating Mode:	Front Operated
Position of Line Terminals:	Top in - bottom out
Power Loss:	Per Pole 13 W
Product Main Type:	OS250

Product Name:	Switch fuse
Rated Operational Current AC-21A (I_e):	(380 ... 415V) 250 A (500V) 250 A (690V) 250 A
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 250 A (690 V) 250 A (500 V) 250 A
Rated Operational Power AC-23A (P_e):	(220 ... 240V) 75 kW (400V) 140 kW (415V) 145 kW (500V) 170 kW (690V) 250 kW
Rated Operational Voltage:	690 V AC
Standards:	IEC
Terminal Type:	Lug terminals

Certificates and Declarations (Document Number)

BV Certificate:	1SCC311103D0201
Declaration of Conformity - CE:	1SCC311095D0201
GL Certificate:	1SCC311097D0201
LR Certificate:	1SCC311102D0201
RoHS Information:	1SCC311108D0202

Classifications

E-number:	3172070
ETIM 5.0:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q

