



SLC ONE 360 R68-83 BL 695TED 927

IP44 36°

One downlight for all applications! Tilts 30° in all directions (360°). For new and rehab projects. Can be mounted into insulation, up to the moisture barrier.

Light technic	
Product ID	SLC1122
Beam angle	36 °
Colour temperature	2700 K, 2700.0 - 2700.0 K
Colour rendering index (CRI/Ra)	90
Type of light source	LED
Lamp efficacy	87 lm/W
MacAdam (SDCM)	3
Rotate	30 °
Tilt-able	360 °
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light sharing	Symmetric
With light source	Yes
Rated luminous flux according to IEC 62722-2-1	695 lm
Colour of light	White
Luminous flux	695.0 - 695.0 lm
Light distributor	Reflector
Technical data	
Type of control signal	Trailing Edge
Exterior color	Black
Dimmable	Yes
Dimming range	1-100% %
Driver output current	180 mA
IP class	IP44
Operating temperature	-10°C ~ +45°C °C
Colour housing	Black
Max. system power	8 W
Adjustability	Rotating and swivelling
Dimming method	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick



05.08.2021

Subject to changes and printing errors

	connection
Voltage type	AC/DC
Strain relief	Yes
Installation	
Cut-out hole (Ø)	68-83 mm
Built-in width	67 mm
Height	45.4 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm
Installation depth	46 mm
Can be installed directly into the insulation	Yes
Type of installation	Recessed
Outer diameter	90 mm
Built-in diameter	68 mm
Suitable for suspended mounting	No
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Suitable for ceiling mounting	Yes
logistics data	
Pcs carton	50
D-pack height	23.2 cm
D-pack width	53.5 cm
Product gross weight	350 g
Imported by	The Light Group
D-pack gross weight	20 kg
Product gross length	111 mm
D-pack length	52 cm
Brand	SLC
Product gross width	101 mm
Product gross height	102 mm
General data	
GTIN	7070938061407
Pallet length	1200 mm
M-pack length	535 mm
F-pack length	100 mm