

T16-0.31



General Information

Extended Product Type:	T16-0.31
Product ID:	1SAZ711201R1013
EAN:	4013614397844
Catalog Description:	T16-0.31 Thermal Overload Relay
Long Description:	The T16-0.31 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the mini contactors or block contactors. Single mounting kits are available as accessory.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Thermal Overload Relays

Accessories

Identifier	Type	Description	Qty
1SAZ701901R0001	DB16	DB16 Single Mounting Kit	1

Ordering

EAN:	4013614397844
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	45.0 mm
Product Net Height:	76.7 mm
Product Net Depth:	53.5 mm
Product Net Weight:	0.100 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	48.0 mm
Package Level 1 Height:	63.0 mm
Package Level 1 Length:	82.0 mm
Package Level 1 Gross Weight:	0.112 kg
Package Level 2 Units:	72 piece
Package Level 2 Width:	280.0 mm
Package Level 2 Height:	210.0 mm
Package Level 2 Length:	395.0 mm
Package Level 2 Gross Weight:	8.450 kg
Package Level 2 EAN:	4013614440540

Technical

Setting Range:	0.23 ... 0.31 A
Rated Operational Voltage:	Auxiliary Circuit 600 V AC DC Main Circuit 690 V AC
Rated Operational Current (I_e):	0.31 A
Rated Operational Current AC-3 (I_e):	0.31 A

Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U_i):	690 V
Number of Poles:	3
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Protected Poles:	3
Conventional Free-air Thermal Current (I_{th}):	Auxiliary Circuit NC 6.00 A Auxiliary Circuit NO 4.00 A
Rated Operational Current AC-15 (I_e):	(120V) NC 3.000 A (120V) NO 0.750 A (240V) NC 3.000 A (240V) NO 0.750 A (400V) NC 0.750 A (400V) NO 0.750 A (500V) NC 0.750 A (500V) NO 0.750 A
Rated Operational Current DC-13 (I_e):	(125V) NC 0.550 A (125V) NO 0.550 A (24V) NC 1.250 A (24V) NO 1.250 A (250V) NC 0.270 A (250V) NO 0.270 A (500V) NC 0.150 A (500V) NO 0.150 A (60V) NC 0.550 A (60V) NO 0.550 A
Degree of Protection:	IP20
Pollution Degree:	3
Connecting Capacity-Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²
Connecting Capacity-Main Circuit:	Flexible with Ferrule 1/2x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm ² Flexible 1/2x 0.75 ... 4 mm ² Solid 1/2x 0.75 ... 1.5 mm ² Solid 1/2x 1.5 ... 4 mm ² Stranded 1/2x 1 ... 4 mm ²
Tightening Torque:	Auxiliary Circuit 1 ... 1.5 N·m Main Circuit 1.1 ... 1.5 N·m
Wire Stripping Length:	Auxiliary Circuit 9 mm Main Circuit 12 mm
Recommended Screw Driver:	Main Circuit Pozidriv 2
Mounting Position:	Position 1 to 5
Power Loss:	Per Pole 1.1 ... 2.0 W
Suitable For:	B6 BC6 B7 BC7 VB6 VBC6 VB7 VBC7 AS09

	AS12
	AS16
Standards:	IEC/EN 60947-1
	IEC/EN 60947-4-1
	IEC/EN 60947-5-1
	UL 60947-1
	UL 60947-4-1

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	Yes
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 22g
Resistance to Vibrations acc. to IEC 60068-2-6:	3g / 3 ... 150 Hz
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Ampere Rating UL/CSA:	0.31 A
Contact Rating UL/CSA:	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Connecting Capacity-Main Circuit UL/CSA:	Flexible 1/2x 18 ... 12 AWG Stranded 1/2x 18 ... 10 AWG
Connecting Capacity-Auxiliary Circuit UL/CSA:	Flexible 1/2x 18 ... 12 AWG Stranded 1/2x 18 ... 12 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 9 ... 13 in·lb Main Circuit 9 ... 13 in·lb

Certificates and Declarations (Document Number)

ABS Certificate:	1SAA941001-0101
BV Certificate:	1SAA941001-0201
CB Certificate:	1SAA941008-2001
CCC Certificate:	1SAA941005-3802
cUL Certificate:	cUL_E48139
Declaration of Conformity - CE:	1SAD938505-0182
DNV Certificate:	1SAA941001-0301
GL Certificate:	1SAA941007-0401
GOST Certificate:	1SAA941000-2704
LR Certificate:	1SAA941001-0501
RINA Certificate:	1SAA941000-0801
RMRS Certificate:	1SAA941000-0703
RoHS Information:	1SAA941005-4402
UL Certificate:	UL_E48139

Classifications

Object Classification Code:	F
E-nummer:	3212057
ETIM 4.0:	EC000106 - Thermal overload relay

ETIM 5.0:

EC000106 - Thermal overload relay

