

**2200 W - 230 mm Low Vibration Heavy Duty Angle Grinder** **D28415**



Autobalancer gives low vibration (4.1m/s<sup>2</sup> triaxially) resulting in greater end user comfort  
Soft start to limit start-up current and reduce kick back  
Anti vibration side handle  
Quick adjustment tool free guard

**Standard Equipment:** Protective tool free guard, Anti vibration side handle, Inner and outer flange set, Spanner

|                    |              |
|--------------------|--------------|
| Power Input        | 2200 Watts   |
| Power Output       | 1540 Watts   |
| No Load Speed      | 6500 rpm     |
| Max. Disc Diameter | 230 mm       |
| Spindle Thread     | M14          |
| Weight             | 6.1 kg       |
| Length x Height    | 450 x 145 mm |



**230mm No volt release switch LAG** **D28498**



No volt release switch prevents the unit starting when plugged in, even if the switch is lock on. Switch must consciously reset before power is delivered  
Torque limiting clutch reduces the maximum torque reaction transmitted to the operator if the disc jams  
Overload protection will prevent the motor overheating by shutting off the unit until the unit cools down  
Soft start to limit start-up current and reduce kick back

**Standard Equipment:** Protective keyless guard, Anti vibration side handle, Inner and outer disc flanges, Spanner

|                    |              |
|--------------------|--------------|
| Power Input        | 2400 Watts   |
| Power Output       | 1246 Watts   |
| No Load Speed      | 6500 rpm     |
| Max. Disc Diameter | 230 mm       |
| Spindle Thread     | M14          |
| Weight             | 5.5 kg       |
| Length x Height    | 490 x 151 mm |



**1800 W - 150 mm Straight Angle Grinder** **DW882**



Abrasion protected high power motor for increased durability  
Rubberized front grip for better control  
Brush access window for better serviceability  
Cut-off brushes to prolong motor life

**Standard Equipment:** Protective guard, Inner and outer disc flanges, Abrasive 150 mm disc, Spanner

|                    |              |
|--------------------|--------------|
| Power Input        | 1800 Watts   |
| Power Output       | 1200 Watts   |
| No Load Speed      | 5600 rpm     |
| Max. Disc Diameter | 150 mm       |
| Spindle Thread     | M16          |
| Weight             | 6.7 kg       |
| Length x Height    | 650 x 155 mm |



**500 W - Single Speed Die Grinder** **D28885**



Short body allows access when grinding in confined spaces  
Hardened, precision-ground collet ensures that all attachments run perfectly true and concentrically  
Cut-off brushes to prolong motor life  
Ergonomic design results in user comfort allowing strain free grinding

**Standard Equipment:** 6 mm collet, Spanner

|                 |             |
|-----------------|-------------|
| Power Input     | 500 Watts   |
| Power Output    | 300 Watts   |
| No Load Speed   | 27000 rpm   |
| Collet Size     | 6 mm        |
| Weight          | 1.4 kg      |
| Length x Height | 250 x 70 mm |
| Spindle lock    | No          |



**Collets**



| Cat. No. | Description |
|----------|-------------|
| D288861  | 3 mm Collet |
| D288862  | 1/8" Collet |
| D288863  | 6 mm Collet |
| D288864  | 1/4" Collet |
| D288865  | 8 mm Collet |

**2200 Watt 355 mm Abrasive Chop Saw** **D28700**



Horizontal handle for superior ergonomics and less user fatigue  
Quick release clamp results in less time in changing the work piece  
High power abrasion protected motor delivers high overload capabilities for greater durability  
Spindle lock for quick and easy wheel change

**Standard Equipment:** Metal cutting disc, Hex key

|                                                    |              |
|----------------------------------------------------|--------------|
| Power Input                                        | 2200 Watts   |
| Power Output                                       | 1350 Watts   |
| No Load Speed                                      | 3800 rpm     |
| Wheel Diameter                                     | 355 mm       |
| Max. Cutting Capacity at 90° [Square Profile]      | 119 x 119 mm |
| Max. Cutting Capacity at 90° [Rectangular Profile] | 115 x 130 mm |
| Max. Cutting Capacity at 90° [L-Shape Profile]     | 137 x 137 mm |
| Max. Cutting Capacity at 90° [Rounded Profile]     | 115 mm       |
| Max. Cutting Capacity at 45° [Square Profile]      | 98 x 98 mm   |
| Max. Cutting Capacity at 45° [Rectangular Profile] | 115 x 98 mm  |
| Max. Cutting Capacity at 45° [L-Shape Profile]     | 98 x 98 mm   |
| Max. Cutting Capacity at 45° [Rounded Profile]     | 98 mm        |
| Weight                                             | 16 kg        |
| Length x Height                                    | 486 x 378 mm |



**2200 Watt 355 mm High Performance Chop Saw** **D28715**



Keyless blade clamp allows quick, hassle free blade change  
Electronic soft start to limit start-up current and kick back reaction  
High power abrasion protected motor delivers high overload capabilities for greater durability  
Keyless mitre adjustments for quick and simple operations

**Standard Equipment:** Metal cutting disc, Hex key, Keyless blade clamp

|                                                    |              |
|----------------------------------------------------|--------------|
| Power Input                                        | 2200 Watts   |
| Power Output                                       | 1350 Watts   |
| No Load Speed                                      | 4000 rpm     |
| Wheel Diameter                                     | 355 x 2.5 mm |
| Max. Cutting Capacity at 90° [Square Profile]      | 120 x 120 mm |
| Max. Cutting Capacity at 90° [Rectangular Profile] | 100 x 200 mm |
| Max. Cutting Capacity at 90° [L-Shape Profile]     | 140 x 140 mm |
| Max. Cutting Capacity at 90° [Rounded Profile]     | 130 mm       |
| Max. Cutting Capacity at 45° [Square Profile]      | 113 x 113 mm |
| Max. Cutting Capacity at 45° [Rectangular Profile] | 100 x 140 mm |
| Max. Cutting Capacity at 45° [L-Shape Profile]     | 120 x 120 mm |
| Max. Cutting Capacity at 45° [Rounded Profile]     | 130 mm       |
| Weight                                             | 18 kg        |
| Length x Height                                    | 520 x 435 mm |



**2200 Watt 355 mm Tungsten Carbide Tipped Metal Cutting Chop Saw** **DW872**



Burr-free cuts at constant cutting depth throughout the life of the blade  
High power 2200 Watt motor with electronic soft start for metal cutting  
Robust cool-running 355 mm, 70 tooth tungsten carbide tipped blade  
Extra wide steel base for larger working area and increased stability

**Standard Equipment:** 355 mm metal carbide blade, Hex key, Auxiliary clamp

|                                                    |              |
|----------------------------------------------------|--------------|
| Power Input                                        | 2200 Watts   |
| Power Output                                       | 1350 Watts   |
| No Load Speed                                      | 1300 rpm     |
| Wheel Diameter                                     | 355 mm       |
| Max. Cutting Capacity at 90° [Square Profile]      | 100 x 100 mm |
| Max. Cutting Capacity at 90° [Rectangular Profile] | 75 x 130 mm  |
| Max. Cutting Capacity at 90° [L-Shape Profile]     | 92 x 92 mm   |
| Max. Cutting Capacity at 90° [Rounded Profile]     | 130 mm       |
| Max. Cutting Capacity at 45° [Square Profile]      | 79 x 79 mm   |
| Max. Cutting Capacity at 45° [Rectangular Profile] | 79 x 123 mm  |
| Max. Cutting Capacity at 45° [L-Shape Profile]     | 56 x 56 mm   |
| Max. Cutting Capacity at 45° [Rounded Profile]     | 79 mm        |
| Weight                                             | 22.5 kg      |
| Length x Height                                    | 525 x 430 mm |



**1200 W - 178 mm Sander** **DW630**



Abrasion protected motor for increased durability  
Dust sealed bearings for long product life  
Precision heat treated gears for smooth power transmission  
Spindle lock for ease of disc changing

**Standard Equipment:** Rubber backing pad, Threaded flange, Two pin spanner, Side handle & guard

|                    |              |
|--------------------|--------------|
| Power Input        | 1200 Watts   |
| Power Output       | 700 Watts    |
| No Load Speed      | 5000 rpm     |
| Max. Disc Diameter | 178 mm       |
| Spindle Thread     | M14          |
| Weight             | 3.2 kg       |
| Length x Height    | 410 x 140 mm |



**1150 W - 178 mm Variable Speed Right Angle Polisher** **DW849**



Full power variable speed electronics with constant speed control  
Abrasion protected high power motor for increased durability  
Heat treated precision gears for smooth power transmission  
Top rubber bumper to protect from scratching the work piece

**Standard Equipment:** Rubber backing pad, Polishing bonnet, Outer flange, Side handle

|                    |              |
|--------------------|--------------|
| Power Input        | 1150 Watts   |
| Power Output       | 670 Watts    |
| No Load Speed      | 0-3000 rpm   |
| Max. Disc Diameter | 178 mm       |
| Spindle Thread     | M14          |
| Weight             | 3.8 kg       |
| Length x Height    | 455 x 135 mm |

