



41097004



SCHUKO socket outlet with LED orientation light enhanced contact protection, Screw-in lift terminals, Berker K.5, stainless steel matt, lacquered

Technical features

| | |
|---|---|
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |
| Power consumption | 0.25 W/0.35 VA |
| Switch-off brightness | ≈ 4 lx |
| Light intensity (white) | 0,2 cd |
| Switch-on brightness | ≈ 2 lx |
| Lighting | additional benefit by combination of a socket outlet with an orientation light |
| Sensor | integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness |
| LED | white LED light ; long service life of the LED |
| Wiring | through-wiring possible, therefore also ideal for retrofitting |
| Imprint | without imprint |
| Installation mode | with spreader claws |
| Type of connection | with screw-in lift terminals |
| Information text | Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets according to VDE 0620-1 |
| Connection terminals | |
| Design | according to DIN 49440 |
| Product description | SCHUKO socket outlet with LED orientation light |
| Designation syntax: differentiation feature 2 | enhanced contact protection |
| Designation syntax: differentiation feature 3 | Screw-in lift terminals |
| Colour | stainless steel matt, lacquered |
| | enhanced contact protection |
| | Screw-in lift terminals |
| Main design line | Berker K.5 |
| Colour of design line | stainless steel |