

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Universal varistor-based plug-in lightning/surge arrester for 3-phase power supply networks with separate N and PE (5-conductor system: L1, L2, L3, N, PE), for Lightning Protection Levels III and IV.

Your advantages

- Quality proven millions of times over in the widest range of applications
- Rapid installation with bridges, thanks to industry-standard overall width of 1 HP
- Easy testing and insulation measurement, thanks to pluggable protection modules
- Can be used in lightning protection level III and IV due to discharge capacity of 12.5 kA per position
- Vibration-resistant latching ensures the plug remains firmly in place

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 2800184 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL1151 |
| Product key | CL1151 |
| Catalog page | Page 46 (C-4-2019) |
| GTIN | 4046356518567 |
| Weight per piece (including packing) | 672.4 g |
| Weight per piece (excluding packing) | 638 g |
| Customs tariff number | 85363030 |
| Country of origin | DE |

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

Technical data

Product properties

| | |
|--------------------------------|---|
| Product type | Arrester combination |
| Product family | VALVETRAB MS |
| IEC test classification | I / II T1 / T2 |
| EN type | T1 / T2 |
| IEC power supply system | TT TN-S |
| Type | DIN rail module, two-section, divisible |
| Number of positions | 4 |
| Surge protection fault message | optical |

Data management status

| | |
|------------------|----|
| Article revision | 11 |
|------------------|----|

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree | 2 |


Electrical properties

| | |
|-------------------------|---------------|
| Nominal frequency f_N | 50 Hz (60 Hz) |
|-------------------------|---------------|

Connection data

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Screw thread | M5 |
| Tightening torque | 3 Nm (1.5 mm ² ... 16 mm ²) 4.5 Nm (25 mm ² ... 35 mm ²) |
| Stripping length | 16 mm |
| Conductor cross section flexible | 1.5 mm ² ... 25 mm ² |
| Conductor cross section rigid | 1.5 mm ² ... 35 mm ² |
| Conductor cross section AWG | 15 ... 2 |
| Connection method | Fork-type cable lug |
| Conductor cross section flexible | 1.5 mm ² ... 16 mm ² |

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 71.2 mm |

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

| | |
|------------------|---------------------------------|
| Height | 89.8 mm |
| Depth | 77.5 mm (incl. DIN rail 7.5 mm) |
| Horizontal pitch | 4 Div. |

Material specifications

| | |
|--|------------------|
| Color | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA 6.6/PBT |
| Material group | I |
| Housing material | PA 6.6 PBT |

Mechanical properties

Mechanical data

| | |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

Protective circuit

| | |
|---|---------------------------|
| Mode of protection | L-N |
| | L-PE |
| | N-PE |
| Direction of action | 3L-N & N-PE |
| Nominal voltage U_N | 240/415 V AC (TN-S) |
| | 240/415 V AC (TT) |
| Nominal frequency f_N | 50 Hz (60 Hz) |
| Maximum continuous operating voltage U_C (L-N) | 335 V AC |
| Maximum continuous operating voltage U_C (L-PE) | 335 V AC |
| Maximum continuous operating voltage U_C (N-PE) | 264 V AC |
| Rated load current I_L | 80 A |
| Residual current I_{PE} | $\leq 5 \mu A$ |
| Standby power consumption P_C | $\leq 810.00 \text{ mVA}$ |
| Nominal discharge current I_n (8/20) μs (L-N) | 12.5 kA |
| Nominal discharge current I_n (8/20) μs (L-PE) | 12.5 kA |
| Nominal discharge current I_n (8/20) μs (N-PE) | 50 kA |
| Maximum discharge current I_{max} (8/20) μs | 50 kA |
| Impulse discharge current (10/350) μs (L-N), charge | 6.25 As |
| Impulse discharge current (10/350) μs (L-N), specific energy | 39 kJ/ Ω |
| Impulse discharge current (10/350) μs (L-N), peak current value I_{imp} | 12.5 kA |
| Impulse discharge current (10/350) μs (L-PE), charge | 6.25 As |
| Impulse discharge current (10/350) μs (L-PE), specific energy | 39 kJ/ Ω |
| Impulse discharge current (10/350) μs (L-PE), peak current value I_{imp} | 12.5 kA |

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

| | |
|--|---|
| Impulse discharge current (10/350) μs (N-PE), charge | 25 As |
| Impulse discharge current (10/350) μs (N-PE), specific energy | 625 kJ/ Ω |
| Impulse discharge current (10/350) μs (N-PE), peak current value I_{imp} | 50 kA |
| Total discharge current I_{total} (8/20) μs | 50 kA |
| Total discharge current I_{total} (10/350) μs | 50 kA |
| Follow current interrupt rating I_{fi} (N-PE) | 100 A |
| Short-circuit current rating I_{SCCR} | 25 kA |
| Voltage protection level U_p (L-N) | ≤ 1.2 kV |
| | ≤ 1.6 kV (30 kA - 8/20 μs) |
| Voltage protection level U_p (L-PE) | ≤ 2 kV |
| Voltage protection level U_p (N-PE) | ≤ 1.7 kV |
| Residual voltage U_{res} (L-N) | ≤ 1.2 kV (at I_n) |
| | ≤ 1.1 kV (at 10 kA) |
| | ≤ 1 kV (at 5 kA) |
| | ≤ 0.9 kV (at 3 kA) |
| Residual voltage U_{res} (L-PE) | ≤ 2 kV (at I_n) |
| | ≤ 1.5 kV (at 10 kA) |
| | ≤ 1.2 kV (at 5 kA) |
| | ≤ 1.1 kV (at 3 kA) |
| Residual voltage U_{res} (N-PE) | ≤ 0.6 kV (at I_n) |
| | ≤ 0.5 kV (at 10 kA) |
| | ≤ 0.5 kV (at 5 kA) |
| | ≤ 0.4 kV (at 3 kA) |
| TOV behavior at U_T (L-N) | 415 V AC (5 s / withstand mode) |
| | 457 V AC (120 min / safe failure mode) |
| TOV behavior at U_T (N-PE) | 1200 V AC (200 ms / withstand mode) |
| Response time t_A (L-N) | ≤ 25 ns |
| Response time t_A (L-PE) | ≤ 100 ns |
| Response time t_A (N-PE) | ≤ 100 ns |
| Max. backup fuse with V-type through wiring | 80 A (gG - 16 mm ²) |
| Max. backup fuse with branch wiring | 160 A (gG) |

Additional technical data

| | |
|---|-------|
| Maximum discharge current I_{max} (8/20) μs | 65 kA |
|---|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 (only when all terminal points are used) |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

| | |
|-----------------------|---|
| Shock (operation) | 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z) |
| Vibration (operation) | 7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

Approvals

UL specifications

| | |
|---|--------------------------|
| Maximum continuous operating voltage MCOV (L-L) | 670 V AC |
| Maximum continuous operating voltage MCOV (L-N) | 335 V AC |
| Maximum continuous operating voltage MCOV (L-G) | 335 V AC |
| Maximum continuous operating voltage MCOV (N-G) | 264 V AC |
| Nominal discharge current I_n (L-L) | 20 kA |
| Nominal discharge current I_n (L-N) | 20 kA |
| Nominal discharge current I_n (L-G) | 20 kA |
| Nominal discharge current I_n (N-G) | 20 kA |
| Mode of protection | L-L L-N L-G N-G |
| Nominal voltage | 415/240 V AC |
| Power distribution system | Wye |
| Nominal frequency | 50/60 Hz |
| Measured limiting voltage MLV (L-L) | 3570 V |
| Measured limiting voltage MLV (L-N) | 2630 V |
| Measured limiting voltage MLV (L-G) | 3600 V |
| Measured limiting voltage MLV (N-G) | 2600 V |
| SPD Type | 4CA |

UL connection data

| | |
|-----------------------------|-------------------------|
| Tightening torque | 30 lb _F -in. |
| Conductor cross section AWG | 14 ... 2 |

Standards and regulations

| | |
|--------------------------|--------------|
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

Mounting

| | |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|


VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2

2800184


<https://www.phoenixcontact.com/gb/products/2800184>

Drawings

Dimensional drawing



Circuit diagram



VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/2800184>



cUL Recognized
Approval ID: FILE E 330181



UL Recognized
Approval ID: FILE E 330181



IECEE CB Scheme
Approval ID: AT 2584



EAC
Approval ID: RU C-DE.*09.B.00169

CCA

Approval ID: NTR-AT 1906



KEMA-KEUR
Approval ID: 2162496-01



DNV GL
Approval ID: TAE00001N9



ÖVE
Approval ID: 18583-009-09

UAE-RoHS

Approval ID: 23-10-88705

cULus Recognized

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27130802 |
| ECLASS-13.0 | 27171201 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000381 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

VAL-MS-T1/T2 335/12.5/3+1 - Lightning/surge arrester type 1/2



2800184

<https://www.phoenixcontact.com/gb/products/2800184>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk