

# PRODUCT DATASHEET

## LN UO 1200 33 W 3000 K

LINEAR ULTRA OUTPUT GEN 1 | Surface luminaire with high luminous efficacy up to 125 lm/W

---

### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Indoor applications
- Industrial and commercial halls
- Public areas
- Corridors, stairwells, basements



---

### Product benefits

- Replacement of conventional T8 luminaires with up to 7100 lm
- Energy savings up to 60 % (compared to luminaires that use fluorescent lamps)
- Robust structure with IK08
- 5 years guarantee

---

### Product features

- Very high luminous efficacy: up to 125 lm/W
- Robust metal housing and PC diffuser
- Wiring at back side of luminaire
- Through wiring possible



## TECHNICAL DATA

### Electrical data

Nominal wattage	33.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	150 mA
Inrush current	20 A
Inrush current time $T_{h50}$	100 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	41
Max. number of luminaires per miniature circuit breaker C10	33
Max. number of luminaires per miniature circuit breaker C16	53
Power factor $\lambda$	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	3700 lm
Luminous efficacy	110 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	$\geq$ 80
Standard deviation of color matching	$\leq$ 5 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °

### Dimensions & Weight

Length	1168.00 mm
Width	62.00 mm
Height	74.00 mm
Product weight	1500.00 g



### Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-10...+40 °C
Type of connection	Screwless terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	40000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	40000 h
Lifespan L90/B10 at 25 °C	30000 h
Number of switching cycles	50000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable









## EQUIPMENT / ACCESSORIES








- Mounting screws and dowels included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LINEAR ULTRA OUTPUT
	On-Pack-Info	Legal Insert Linear LED UO
	Legal information	LINEAR ULTRA OUTPUT 1200
	Legal information	LS Insert Linear Ultra Output
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	LN UO
	Declarations of conformity UKCA	LN UO 1200
Photometric and lighting design files		Document name
	IES file (IES)	LINEAR UO 1200 33W 3000K IES



Photometric and lighting design files		Document name
	LDT file (Eulumdat)	LINEAR UO 1200 33W 3000K LDT
	ULD file (DIALux)	LINEARULTRAOUTPUT120033W3000K
	ROLF file (RELUX)	LN UO 1200 33W-3000K
	UGR file (UGR table)	LINEAR UO 1200 33W 3000K LDT
CAD/BIM files		Document name
	BIM Revit 3D	Linear Ultra Output
	CAD STEP 3D	LN UO 1200
Tender texts		Document name
	Tender documents	LINEAR ULTRA OUTPUT 1200 33 W 3000 K-EN

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075122147	Folding box 1	69 mm x 1,174 mm x 77 mm	1345.00 g	6.24 dm <sup>3</sup>
4058075122154	Shipping box 6	1,184 mm x 225 mm x 170 mm	8725.00 g	45.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**ADDITIONAL CATALOG INFORMATION**



## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.