

# PRODUCT DATASHEET

## Flex COB 5M 3000K

Flex Strips COB Warm White | Decorative COB Strips with warm white light and homogenous lighting effect



---

### Areas of application

- Living areas
- Indirect lighting

---

### Product benefits

- Easy and quick installation
- Homogenous lighting thanks to COB LED

---

### Product features

- COB technology for homogeneous light distribution
- Light color: Warm White
- Flexible, bendable LED strips



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	24.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	130.000 mA
Inrush current	28 mA
Power factor $\lambda$	> 0.5
Total harmonic distortion	< 70 %
Protection class	II

### Photometrical data

Luminous flux	2100 lm
Total luminous flux of contained light sources	2100 lm
Luminous efficacy	87 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	170 °

### Dimensions & Weight

Length	5000.00 mm
Width	8.00 mm
Height	1.60 mm
Product weight	150.00 g

FLEX COB 5M

### Materials & Colors

Product color	Yellow
Housing color	Yellow
Body material	Silicone
Cover material	Silicone
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE
Replaceable light source (EPREL)	Not replaceable




### EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

### Safety advice

– To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

### DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	FLEX COB WHITE
 Legal information	Legal Insert FLEX COB
 Declarations of conformity	CE Declaration Flex COB and Audio

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854095269	Folding box 1	65 mm x 140 mm x 141 mm	192.00 g	1.28 dm <sup>3</sup>
4099854095276	Shipping box 8	306 mm x 282 mm x 173 mm	1934.00 g	14.93 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.