

Air-tight cavity wall installation



LUFTDICHT



O-range ECON® 64 one-gang junction box, air-tight, Depth 62 mm, halogen-free

- Air-tight design with sealing membranes
- Fully insulated, air-tight through-wiring for combinations using support connectors
- Toolless cable or conduit entries
- Integrated cable retention of NYM cables, self-locking of conduits

Article no:	9264-78
EAN:	4013456548305
For panel thickness	7 - 40 mm
Depth	62 mm
Cut hole Ø	68 mm
Device screws	2
Tube entries up to Ø 25 mm	2
Cable entries 5 x 2.5 mm ² or 7 x 1.5 mm ²	1
Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ²	2
Cable entries 3 x 1.5 mm ²	3
Support connectors for each package	7
Air-tight	Yes
Halogen-free	Yes
Packaging inner/dispatch	25/250

Air-tight O-range® cavity wall boxes with ECON® technology for energy-efficient electrical installation according to GEG. The elastic ECON® technology sealing membrane allows air-tight electrical installation.

- Elastic sealing membrane for guaranteed air-tightness
- Innovative clamp technology with integrated cable retention
- Toolless cable and conduit entry
- Air-tight combined with support connector

O-range ECON®    