


eNet wireless control unit 1 – 10 V, 1-gang Mini



| Specification | Order No. | Packing unit | PS | EAN |
|---|-----------|--------------|----|---------------|
|  | 5421 00 | 1/5 | 02 | 4010337774174 |

Features

- The eNet wireless control unit enables the switching and brightness setting of lights with 1 - 10 V interface.
- Switch-on and minimum brightness can be saved.
- Scene operation.
- Status display of the 1 - 10 V devices via LED.
- Status feedback to eNet wireless transmitter.

Can be set with eNet server:

- Maximum brightness.
- Dimming speed.
- Delay time.
- Switch-on/off delay.
- Dimming ramp up/down.
- Switch-off pre-warning.
- Permanent-on, permanent-off.
- Hotel function.
- Light control.
- Repeater function.

Can be set with eNet server:

- Localisation of the device.

Technical data

| | |
|----------------------|--------------------|
| Rated voltage: | AC 230 V, 50/60 Hz |
| Standby: | max. 0.5 W |
| Ambient temperature: | -25 °C to +70 °C |
| Control current: | max. 50 mA |
| Switching current | |
| - Ohmic load: | 6 A |

| | |
|----------------------|------------------------|
| - Fluorescent lamps: | 3 AX |
| Connected load | |
| - Ohmic load: | 1380 W |
| - Capacitive load: | 690 VA (560 μ F) |
| Connections: | max. 4 mm ² |
| Wireless frequency: | 868.0 to 868.6 MHz |
| Range (free field): | approx. 100 m |

Notes

- Installation in device box, surface-mounted housing, or in an installation adapter.
 - Wireless approval is valid for EU and EFTA countries.
-

Dimensions in mm

Ø 53 H 28
