



SLC Universal LED-dimmer TED

03/11/2022

S56001

Product description

Trailing Edge. 220-240VAC 50Hz. 10-350W (1.5A max). End Turning function.

Trailing Edge. 220-240VAC 50Hz. 10-350W (1.5A max). End Turning function. Fits in wall box and in standard frame. Ability to adjust minimum level.

Technical data

Method of operation	Turn button
Dimming phase cut-on	No
Serial dimmer	No
Substation input	No
Applicable with button	No
Applicable with presence indicator	Yes
Applicable with transmission button	No
Mounting method	Flush mounted (plaster)
Material	Plastic
Halogen free	No
Surface finishing	Glossy
Transparent	No
Nominal voltage	220 - 240 V
Nominal power	10 - 350 VA
Core cross section	1 - 2 mm ²

App control via Bluetooth	No
Dimming phase cut-off	Yes
Type of load	Universal and LED Retrofit
Light value memory	Yes
Applicable with movement sensor	Yes
Applicable with time switch/timer	Yes
Applicable with infrared button	No
Type of fastening	Mounting with claw and screw
Material quality	Duroplast
Surface protection	Untreated
Colour	White
Suitable for degree of protection (IP)	IP20
Frequency	50 - 60 Hz
Connection type	Screwed terminal
Width of device	83,5 mm





Height of device	83,5 mm
Min. depth of built-in installation box	25 mm
Tunable White	No
Expected lifetime (Hours) (Ta 25°C)	110000
Dimming interface	Trailing edge
Brand	SLC
Produced by	The Light Group

Depth of device	44 mm
Mono	Yes
RGBW	No
Expected lifetime (Hours) (Ta 45°C)	50000
Dimming range	1-100%
GTIN	7070938055017
HS Code	85437003