

PRODUCT-DETAILS

MPR32/1

Modular Combi Plastic, 1x16A 3P+N+E, 1x32A 3P+N+E, 250x430x160, 3x2P Schuko outlet 10/16A, MCB+RCD, IP44



General Information

Extended Product Type	MPR32/1
Product ID	2CMA106211R1000
EAN	7392696062114
Catalog Description	Modular Combi Plastic, 1x16A 3P+N+E, 1x32A 3P+N+E, 250x430x160, 3x2P Schuko outlet 10/16A, MCB+RCD, IP44
Long Description	Modular Combi Plastic, 1x16A 3P+N+E, 1x32A 3P+N+E, 250x430x160, 3x1P+E Schuko outlet 10/16A, IP44, RCD F204 A-63/0,03, 3xMCB S201-C16, 1xMCB S203-C16, 1xMCB S203-C32, Cable entry, 4 knock-outs at the top, 2xØ40,5mm and 2xØ25,5mm, Three at the bottom 2xØ40,5mm, 1xØ47,5mm

Ordering

E-Number (Sweden)	E2466474
EAN	7392696062114
Country of Origin	Czech Republic (CZ)

Dimensions

Product Net Width	250 mm
Product Net Height	430 mm
Product Net Depth /	160 mm

Length	
Product Net Weight	5.0 kg

Container Information

Package Level 1 Width	210 mm
Package Level 1 Depth / Length	270 mm
Package Level 1 Height	490 mm
Package Level 1 Gross Weight	5.320 kg
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0004
Declaration	2CMC700005D0004
Environmental Information	2CMC000057M0000
REACH Declaration	2CMC700005D0004

Additional Information

Additional Information	Cable entry, 4 knock-outs at the top, 2xØ40,5mm and 2xØ25,5mm, Three at the bottom 2xØ40,5mm, 1xØ47,5mm
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 mm ²
Cable Entry Position	Cable entry, 4 knock-outs at the top, 2xØ40,5mm and 2xØ25,5mm, Three at the bottom 2xØ40,5mm, 1xØ47,5mm
Cable Length	0 m
Color	Grey
Connection Type	Screw Clamp
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Modular Combi
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#MPR32/1
Mounting Holes	200x472
Mounting Type	Wall mounting
Number of RCDs 30mA	1
Order Multiple	1 piece
Product Main Type	MPR
Product Name	Modular Combi
Rated Current (I _n)	32 A
Rated Residual Current	30 mA
Rated Voltage (U _r)	346 ... 415 V
Recommended Screw Driver	PH2

Standards	IEC 61439-1 IEC 61439-2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000026M0001
Installation Manual	2CMC000026M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440501
UNSPSC	39120000

Technical

Wiring Diagram	9AKK107680A1924
----------------	-----------------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Modular Combination Boxes

