



Outdoor walk-over luminaire for ground surface installation
 Max. load pressure 500 kg
 Material: low copper content die-cast aluminium
 Diffuser: UV resistant opal polycarbonate
 External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately
 PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately
 Light source: LED unit / Side emitter optic to direct the light along the ground surface
 Anticorodal anodized aluminium cable gland with watertight internal resin coating - AQUASTOP system / Luminaire supplied with 1,5 m polyurethane buriable cable 2x0,8
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 78 x H 27 mm
Light source	LED
Wattage	3 W
Power supply	24 Vdc
Light source output	300 lm
System output	65 lm
System efficiency	22 lm/W
Color Rendering Index – CRI	≥80
LED energy class	D
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 67
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Weight	0.25 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
		4K	4000K

on request:

CO	CORTEN
BR	BRONZE

ACCESSORIES

