



| | |
|-----------------------------------|-----------------------|
| SKU | : 701GB93030D0 |
| Housing Material | : Extruded Aluminum |
| Housing Colour | : Black (RAL 9005) |
| Luminaire Dimension [mm] | : 347x76.8x40mm |
| Cut-Out [mm] | : N/A |
| Optic | : Reflector |
| Reflector Colour | : Specular Aluminium |
| Beam Angle [deg] | : 30° |
| LED Power [W] | : N/A |
| System Power [W] | : 19.5W |
| Luminous Flux [lm] | : 1650lm |
| System Efficiency [lm/W] | : 85lm/W |
| Light Source | : 930 (3000K / CRI90) |
| CCT [K] | : 3000K |
| CRI [Ra] | : 90 |
| Chromaticity Tolerance | : 3 MacAdam |
| Mains Voltage [VAc] | : 220-240V / 50-60Hz |
| Power Supply | : DALI |
| Nominal Current [mA] | : N/A |
| Forward Voltage [V] | : N/A |
| Ambient Temperature [degC] | : 35°C |

| | |
|----------------------------------|-----------|
| Ingress Protection | : IP20 |
| Lifetime/Failure Rate [h] | : 50000h |
| Electrical Safety Class | : Class I |
| Net Weight [Kg] | : 1.3Kg |
| Certificates/Declarations | : CE/UKCA |
| Warranty [Y] | : 5Y |

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.