



Recessed LED fitting IP65

MODUS LAB4000, IP65, recessed into raster 600, square A, prismatic cover, LED 830, NONSELV, DALI driver 350mA,

Code: LAB4000A3KN600DALI
EAN: 8596099043513



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	4400
System power (W):	32	Luminaire efficacy (lm/W):	138
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP65
Color housing:	White	Material housing:	Steel
Light source included:	Yes		
Suitable for built-in mounting:	Yes		
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, removeable ballast

Optical system

Optical system:	KN	Light outlet:	Direct
Anti-glare limiting UGR:	19	Light sharing:	Symmetric
Material cover:	Plastic, structured		

Dimensions

Length (mm):	596	Width (mm):	596
Height/depth (mm):	85	Built-in height/depth (mm):	85
Raster (mm):	600	Weight (kg):	5,4

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	Dimming DALI:	Yes
Indoor use only:	Yes		