


LED waterproof light fitting

MODUS PL 2500, wide body 675mm, LED 830 , body PE, opal PC cover, IP65, driver 700mA

Code: PL2500S2W3ND

EAN: 8596099006020



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	2750
System power (W):	20	Luminaire efficacy (lm/W):	138
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes		
Material housing:	Plastic		
Light source included:	Yes	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Rated ambient temperature (°C):	-10...+45
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast

Optical system

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

Dimensions

Length (mm):	675	Width (mm):	135
Height/depth (mm):	100	Weight (kg):	1,5

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	No dim function:	Yes
Indoor use only:	Yes		