

LED downlight with opal cover

**MODUS SPMI3000, LED 830, 700mA non-dim, metal white ring 240mm**



**Code:** SPMI3000KO3V2DB/ND

**EAN:** 8595073795677

This product contains a light source with energy efficiency class D



## Luminaire properties

Product category:	Downlight/spot/floodlight	Effective luminous flux (lm):	3350
System power (W):	28	Luminaire efficacy (lm/W):	120
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP43
Color housing:	White	Surface protection:	Powder coating
Material housing:	Aluminium		
Light source included:	Yes		
Suitable for built-in mounting:	Yes	Made in Czech republic:	Yes

## Light source

Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Colour consistency (McAdam ellipse):	SDCM3
Replaceability:	Removeable light source, replaceable ballast		
Light source type:	224060405	Energy efficiency class:	D

## Optical system

Optical system:	SPMI	Light outlet:	Direct
Reflector:	High-gloss	Light sharing:	Symmetric
Material cover:	Glass opal		

## Dimensions

Outer diameter (mm):	<b>240</b>	Height/depth (mm):	<b>87</b>
Built-in height/depth (mm):	<b>87</b>	Built-in diameter (mm):	<b>225</b>
Weight (kg):	<b>2</b>		

## Electrical values

Protection class:	<b>II</b>	Connection type:	<b>Pinching contact</b>
Voltage type:	<b>AC</b>	Type of control gear:	<b>LED operating device current-controlled</b>
Nominal voltage (V):	<b>220...240</b>	Control gear included:	<b>Yes</b>
Type of wiring:	<b>Ending</b>	No dim function:	<b>Yes</b>