



WNA301



### Cubyko LT shutter push-button with stop symbol composable grey IP55

#### Technical Features

##### Electric current

|                           |      |
|---------------------------|------|
| Momentary contact current | 10 A |
|---------------------------|------|

##### Voltage

|               |       |
|---------------|-------|
| Rated voltage | 250 V |
|---------------|-------|

##### Frequency

|           |            |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

##### Architecture

|                           |               |
|---------------------------|---------------|
| Control/operation element | Double rocker |
|---------------------------|---------------|

##### Materials

|                |               |
|----------------|---------------|
| Colour         | Grey          |
| Surface finish | Satin finish  |
| Material       | Thermoplastic |
| Treatment      | Untreated     |
| Transparent    | No            |

##### Dimensions

|                                    |       |
|------------------------------------|-------|
| Height                             | 75 mm |
| Width                              | 75 mm |
| Depth                              | 32 mm |
| Built-in depth flush-mounted boxes | 40 mm |

##### Installation, mounting

|             |                |
|-------------|----------------|
| Mounting on | Flush mounting |
|-------------|----------------|

##### Controls and indicators

|                              |                    |
|------------------------------|--------------------|
| Number of buttons            | 2                  |
| Type of push button          | Single push button |
| With feedback signal contact | No                 |

##### Connectivity

|                    |              |
|--------------------|--------------|
| Type of connection | quickconnect |
|--------------------|--------------|

##### Connection

|                     |                 |
|---------------------|-----------------|
| Connector/plug type | Turn screw lock |
|---------------------|-----------------|

##### Safety

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP20 |
| Impact resistance IK          | IK05 |

##### Accessories

|                     |    |
|---------------------|----|
| Has labelling field | No |
|---------------------|----|

##### Use conditions

|                       |             |
|-----------------------|-------------|
| Operating temperature | -15 - 30 °C |
|-----------------------|-------------|

##### Texts

|                    |                                                                       |
|--------------------|-----------------------------------------------------------------------|
| Imprint            | With imprinted symbol arrow                                           |
| Installation mode  | For screw fastening                                                   |
| Switch mode        | With mechanical and electrical interlock to prevent mutual activation |
| Type of connection | With plug-in terminals                                                |

##### Suitable for

|        |  |
|--------|--|
| cubyko |  |
|--------|--|

Sustainability

|                 |     |
|-----------------|-----|
| Halogen free    | Yes |
| REACH-SVHC free | Yes |
| RoHS conform    | Yes |