



WNA402

**cubyko Double horizontal flush adapter grey IP55**

**Technical Features**

**Capacity**

|                   |   |
|-------------------|---|
| Number of gangs   | 2 |
| Number of modules | 2 |

**Materials**

|                |               |
|----------------|---------------|
| Colour         | Light grey    |
| RAL code       | 7035          |
| Surface finish | Matt          |
| Material       | Thermoplastic |
| Treatment      | Untreated     |

**Dimensions**

|  |        |
|--|--------|
| Height                                     | 154 mm |
| Width                                      | 83 mm  |
| Depth                                      | 38 mm  |
| Height of P-touch band for labelling field | 0 mm   |

**Accessories**

|                     |    |
|---------------------|----|
| Has labelling field | No |
|---------------------|----|

**Installation, mounting**

|                               |                |
|-------------------------------|----------------|
| Mounting on                   | Flush mounting |
| Mounting-/Connection Position | Horizontal     |

**Safety**

|                               |                        |
|-------------------------------|------------------------|
| Ingress Protection (IP) class | IP20                   |
| Usable in higher IP class     | IP55 with closed cover |
| Impact resistance IK          | IK05                   |

**Use conditions**

|                       |             |
|-----------------------|-------------|
| Operating temperature | -15 - 30 °C |
|-----------------------|-------------|

**Texts**

|                   |  |
|-------------------|--|
| Installation mode | With clamp/screw fastening<br>With mounting adapter and sealing<br>For flush-mounted and hollow wall mounting<br>For vertical mounting |
|-------------------|--|

**Sustainability**

|                 |     |
|-----------------|-----|
| Halogen free    | Yes |
| REACH-SVHC free | Yes |
| RoHS conform    | Yes |