

# Socket outlet 2-way base QC white 9003

Reference STA501000



Activity  
Product family  
Brand  
Range

Installation systems  
Wiring devices  
Stago  
WGX-W

## Base

Activity	Installation systems
Product family	Wiring devices
Brand	Stago
Range	WGX-W
GTIN	7321679003028

## Commercial and Web

Wiring Device Component Type	W815Q
Colour	White RAL9003
Short description	Socket outlet 2-way base QC white 9003
Medium description	Socket outlet 2-way base quick connect F80 - with label window - plastic halogen free - white RAL9003
Length	116 mm
Width	84 mm
Height	52 mm
Material	Plastic

## ETIM (EC000125-Socket outlet)

Model (EF000010)	EV024206
Protective contact (EF001033)	*
Protective earth pin round (EF012000)	*
Number of active pins (round) (EF011998)	4

Number of active pins (flat) (EF011999)	0
With signal lamp (EF000198)	No
With built (EF009258)	No
Type of USB power supply (EF015873)	*
Number of units (EF000074)	*
Number of modules (module system) (EF009573)	*
Number of socket outlets switchable (EF008814)	0
Number of phases (EF000351)	1
Imprint/indication (EF003823)	None
Connection type (EF000124)	Push-in clamp
With hinged lid (EF000117)	No
With enhanced contact protection (EF000389)	Yes
Label space/information surface (EF001035)	Yes
Colour (EF000007)	White
RAL (EF003882)	9003
Metallic colour (EF015260)	No
Transparent (EF006243)	No
Lockable (EF000113)	No
Eject (EF001051)	No
Insulated mounting (EF001588)	Yes
With function lighting (EF008861)	No
With orientation lighting (EF008862)	No
Over voltage protection (EF001332)	No
Fault current protection (EF001333)	No
With miniature fuse (EF006571)	No
Special power supply (EF001334)	*
Mounting method (EF000003)	Wall duct
Type of fastening (EF002442)	Snap mounting (engagement)
Material (EF002169)	Plastic
Material quality (EF001257)	Thermoplastic
Halogen free (EF000025)	Yes
Surface protection (EF000139)	Untreated
Surface finishing (EF006569)	Matt
Anti (EF023790)	No
With on/off switch (EF000488)	No
With loop through function (EF006604)	No
Rotated central insert (EF001331)	Yes
Nominal current (EF000001)	16 A
Nominal voltage (EF000002)	250 V
Frequency (EF000416)	50 - 50 Hz
Rated fault current (EF002358)	* mA
Suitable for degree of protection (IP) (EF006755)	IP20
Impact strength (EF004293)	*
Device width (EF008808)	116 mm
Device height (EF008809)	84 mm

Device depth (EF008810)	50 mm
Compatible with Apple HomeKit (EF014925)	No
Compatible with Google Assistant (EF014926)	No
Min. depth of built (EF012278)	52 mm
Compatible with Amazon Alexa (EF014927)	No
IFTTT support available (EF011072)	No
For heavy conditions (according to VDE) (EFDE0005)	No

---

## Logistic

Pack 1 type	Bag
Quantity pack 1	1
Weight pack 1	0.17 kg
Length pack 1	116 mm
Width pack 1	84 mm
Height pack 1	52 mm
Pack 2 type	Carton
Quantity pack 2	10
Weight pack 2	2.07 kg
Length pack 2	330 mm
Width pack 2	240 mm
Height pack 2	90 mm
Pack 3 type	Carton
Quantity pack 3	40
Weight pack 3	8.3 kg
Length pack 3	395 mm
Width pack 3	260 mm
Height pack 3	350 mm
Pack 4 type	Pallet
Quantity pack 4	720
Weight pack 4	155 kg
Length pack 4	1200 mm
Width pack 4	800 mm
Height pack 4	870 mm
Customs code	85366990
Net weight	0.17 kg
Country of origin	CN

---

## Certification

ETIM class	EC000125
------------	----------

---

## Status product

Product status	Commercialized
----------------	----------------

---

Environmental

GWP Total A1-A3

1.97974 kgCO2e

---

For the latest information check [http://wibe-group.com/cable-support-systems/installation-systems/wiring-devices/socket-outlets\\_wd/socket-outlet-2-way-master-qc-white](http://wibe-group.com/cable-support-systems/installation-systems/wiring-devices/socket-outlets_wd/socket-outlet-2-way-master-qc-white)

This information is meant as an indication and cannot be used to ensure fitness with any solution. This file is subject to change, for detailed information, please contact our Customer Service.