

# Junistar Lux IsoSafe



## Junistar Lux IsoSafe Brushed steel 580lm 2700K Ra 98 Trailing edge dimming

Article code: 902521  
 EAN: 7021989025214  
 Replaces: 901202



### Electrical

Wattage: 7W  
 System wattage: 8W  
 Voltage: 220-240V  
 Frequency (Hz): 50/60Hz  
 Max. luminaires per circuit breaker: B10: 105, B16: 168, C10: 105, C16: 168

### Light technic

Type of light source: LED  
 Luminous flux: 580lm  
 Efficacy: 73 lm/W  
 Colour temperature: 2700K  
 Colour rendering (CRI): Ra 98  
 MacAdams factor: SDCM: 1  
 Lifetime: L90/B10>100,000  
 Light distribution: Direct  
 Optic: Reflector  
 Beam angle: 42°  
 UGR: UGR<22

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class II SELV  
 IP Class: IP44/IP20

### Energy and approvals

Contains light source of energy class: F  
 Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
 Colour: Brushed steel  
 Optics: Tempered glass

### Mounting/Connection




Mounting: Recessed, Indoor  
 Connection: Screwless terminal block

### Dimensions

Height (mm) H: 56  
 Diameter (mm) D: 94  
 Cut-out (mm): 83  
 Ceiling void depth (mm): 54  
 Weight (kg) gross/net: 0.415 / 0.349

### Packaging

Packing dimensions (mm): 130 x 115 x 75



cd/km η = 100 %

— C0/C180  
 — C90/C270



7 0 2 1 9 8 9 0 2 5 2 1 4